

Declaration of Performance

LE/DoP-Nr. 059E/CPR/2024-07-15

- 1. **Unique identification of the product type:** Mortise lock 12302
Mortise lock 12312
Mortise lock 12430
Mortise lock 12511
- 2. **Intended use:** Panic exit devices operated by a horizontal bar, for use on escape routes
- 3. **Manufacturer:** Glutz Ltd.
Glutz Segetzstrasse13
CH-4502 Solothurn
Switzerland
- 4. **Authorised representative:** ./.
- 5. **Systems of assessment of constancy of performance:** System 1
- 6. **Harmonised standard:** EN 1125: 2008
Notified body: **PfB** Rosenheim NB-Nr. 1644 as issued the Certificate of constancy of performance with the number 057-1644-CPR-24-004 to system 1 and essential characteristics assessed from 7.1 to 7.6.
- 7. **Declared performance:**

Essential characteristics	Performance	Harmonised technical specification
7.1 Ability to release (for doors on escape routes)	fulfilled (≤ 80N unloaded) (≤ 220N loaded)	4.2.1 EN 1125: 2008
7.2 Durability of ability to release against aging and degradation (for doors on escape routes)	fulfilled (200.000 cycles)	4.2.1 EN 1125: 2008
7.3 Self-closing ability C (for fire/smoke doors on escape routes)	-	4.2.1 EN 1125: 2008
7.4 Durability of ability to release regarding Self-closing ability C against aging and degradation (for fire/smoke doors on escape routes)	-	4.2.1 EN 1125: 2008
7.5 Fire resistance E (integrity) and I (insulation) (for fire doors on escape routes)	-	4.2.1 EN 1125: 2008
7.6 Control of dangerous substances	-	4.1.25, EN 1125: 2008 Note 1 in ZA. 1

- 8. The performance of the actual product is in conformity with the declared performance / performances. The issue of the declaration of performance complying with regulation (EU) nr. 305/2011 is under the sole responsibility of the above-named manufacturer.

Solothurn, 15.07.2024

Stefan Häni, Head of Development Mechanic