

## Declaration of Performance

LE/DoP-Nr. 030EN/CPR/2025-02-28

1. **Unique identification of the product type:** Mortise Locks & Multipoint Locks  
18945,18947,18905,18990,18920,18995,18962,18970,18971,  
18907,18970HZ,18971HZ,18945HZ,18947HZ,18962HZ
2. **Intended use:** Emergency exit devices operated by a lever handle or push pad,  
for use on escape routes
3. **Manufacturer:** Glutz AG  
Segetzstrasse 13  
CH-4502 Solothurn  
Switzerland
4. **Authorised representative:** ./.
5. **Systems of assessment of constancy of performance:** System 1
6. **Harmonised standard:** EN 179:2008
- Notified body:** **PfB** Rosenheim NB-Nr. 1644 as issued the Certificate of constancy of performance with the number 1644-CPR-057-24-003 to system 1 and essential characteristics assessed from 7.1 to 7.6.

### 7. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
7.1 Ability to release (for doors on escape routes)	fulfilled (≤ 70N unloaded)	4.2.1 EN 179:2008
7.2 Durability of ability to release against aging and degradation (for doors on escape routes)	fulfilled (200.000 cycles)	4.2.1 EN 179:2008
7.3 Self-closing ability C (for fire/smoke doors on escape routes)	-	4.2.1 EN 179:2008
7.4 Durability of ability to release regarding Self-closing ability C against aging and degradation (for fire/smoke doors on escape routes)	-	4.2.1 EN 179:2008
7.5 Fire resistance E (integrity) and I (insulation) (for fire doors on escape routes)	-	4.2.1 EN 179:2008
7.6 Control of dangerous substances	-	4.1.29, EN 179:2008 Note 2 in ZA 1

8. The performance of the actual product is in conformity with the declared performance / performances. The issue of the declaration of performance complying with regulation (EU) nr. 305/2011 is under the sole responsibility of the above-named manufacturer.

Solothurn, 28.02.2025



Marco Hauri  
CEO



Stefan Häni  
Head of Development Mechanic