

## Declaration of Performance

LE/DoP-Nr. 059EN/CPR/2025-02-28

- 1. Unique identification of the product type:** Mortise Locks  
12300,12302,12310,12312,12340,12400,12410,  
12430,12500,12501,12511,12402,12412,12100
- 2. Intended use:** Panic exit devices operated by a horizontal bar, for use on escape routes
- 3. Manufacturer:** Glutz AG  
Segetzstrasse 13  
CH-4502 Solothurn  
Switzerland
- 4. Authorised representative:** ./.
- 5. Systems of assessment of constancy of performance:** System 1
- 6. Harmonised standard:** EN 1125:2008
- Notified body:** PFB Rosenheim NB-Nr. 1644 as issued the Certificate of constancy of performance with the number 1644-CPR-057-24-004 to system 1 and essential characteristics assessed from 7.1 to 7.6.

### 7. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
7.1 Ability to release (for doors on escape routes)	fulfilled (≤ 80N unloaded) (≤ 220N loaded)	4.2.1 EN 1125:2008
7.2 Durability of ability to release against aging and degradation (for doors on escape routes)	fulfilled (200.000 cycles)	4.2.1 EN 1125:2008
7.3 Self-closing ability C (for fire/smoke doors on escape routes)	-	4.2.1 EN 1125:2008
7.4 Durability of ability to release regarding Self-closing ability C against aging and degradation (for fire/smoke doors on escape routes)	-	4.2.1 EN 1125:2008
7.5 Fire resistance E (integrity) and I (insulation) (for fire doors on escape routes)	-	4.2.1 EN 1125:2008
7.6 Control of dangerous substances	-	4.1.25, EN 1125:2008 Note 1 in ZA 1

- 8.** The performance of the actual product is in conformity with the declared performance / performances. The issue of the declaration of performance complying with regulation (EU) nr. 305/2011 is under the sole responsibility of the above-named manufacturer.

Solothurn, 28.02.2025

  
Marco Hauri  
CEO

  
Stefan Häni  
Head of Development Mechanic