

Certificate of Constancy of Performance



Certificate No.: 0757-CPR-229PANIK-6014391-4-9

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

Basis:

EN 1125:2008-01

Panic exit devices

Product description/
specification

GLUTZ

According to configuration in **annex 1**

Levels and classes of
performance

According to configuration in **annex 1**

Intended use(s)

Intended for use on doors in escape routes with requirements for fire resistance and smoke control

placed on the market
under the name or trade
mark of

Glutz AG

Segetzstr. 13, CH-4502 Solothurn

and produced in the
manufacturing plant(s)

Glutz AG

Segetzstr. 13, CH-4502 Solothurn

Notified body No.
EC-Reference-No.

0757

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 1125 : 2008


under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the **constancy of performance of the construction product**.

This certificate was first issued on 01.01.2017 and will remain valid until 17.03.2026, as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The use of this certificate and the marking of the products are bound by an existing certification and surveillance contract with the **ift** Rosenheim no. 229PANIK 6014391.

Christian Kehrer

Christian Kehrer
Head of notified product certification body
ift Rosenheim
22.03.2023



www.ec.europa.eu

Identity check



www.ift-rosenheim.de/
ift-zertifiziert
ID: 38F-24D11

Certificate of constancy of performance

Annex 1 Page 1 of 8
 Certificate holder: Glutz AG
 Date of issue: 22.03.2023



Certificate No.: 0757-CPR-229PANIK-6014391-4-9

Intended use and essential characteristics:

Use on doorsets on escape routes

Essential characteristic	Clauses with requirements in EN 1125:2008	Performance of the product
Ability to release (for locked doors on escape routes)	4.2.1 Thresholds as per Table 1 Release function Bar design Bar projection Field of door application Door mass and dimensions Outside access device Release forces Security requirements (Burglar resistance)	$\leq 1S$: Pass Type A (push-bar): Pass $w \leq 100\text{mm}$ or 150mm depending on model Grade A, B or C: Pass Pass Grade 7: (Door mass 200 kg): Pass (Dimensions 1,320 mm in width, 2,520 mm in height): Pass Pass ($\leq 80\text{ N}$, $\leq 220\text{ N}$ under pressure): Pass (Grade 2, 1,000 N) Pass
Durability of ability to release against aging and degradation (for doors on escape routes)	4.2.1 Thresholds as per Table 1 Corrosion resistance Temperature range Re-engagement force Durability Abuse resistance of operating device Final examination	Pass Grade 3 (96h, $\leq 120\text{ N}$) Pass ($-10\text{ }^{\circ}\text{C}$ to $+60\text{ }^{\circ}\text{C}$, $\leq +50\%$) Pass ($\leq 50\text{ N}$) Pass (Field of door application Grade B: 200,000 cycles, Grade 7) Pass (500 N, 1,000 N): Pass (Release force ($\leq 80\text{ N}$, $\leq 220\text{ N}$ under pressure): Pass (Door face gap $R \leq 25\text{ mm}$): Pass Free door movement) Pass
Self-closing ability C (for fire/smoke doors on escape routes)	4.2.1 Thresholds as per Table 1 Re-engagement force	($\leq 50\text{ N}$) Pass
Durability of self-closing ability C against aging and degradation (for fire/smoke doors on escape routes)	4.2.1 Thresholds as per Table 1 Durability Re-engagement force	(Field of door application Grade B: 200,000 cycles, Grade 7): Pass ($\leq 50\text{ N}$) Pass
Resistance to fire E (integrity) and I (insulation) (for fire doors on escape routes)	4.2.1 Thresholds as per Table 1 Annex B	Grade B: Pass Grade 0: npd

Annex 1 **Page 2 of 8**
Certificate holder: **Glutz AG**
Date of issue: **22.03.2023**



Certificate No.: 0757-CPR-229PANIK-6014391-4-9

Panic exit devices as per DIN EN 1125 for doorsets
Designation:

GLUTZ panic exit devices

No.	Item	Function	Backset	Distance	Forend	Accessories	Classification
1	24000	I	60-80 mm	PC 78 mm RC 78 mm	18/20 mm	Strike plates: GLUTZ B1130 GLUTZ B1138	3 7 6 B 1 3 2 1 A B
2	24010						
3	24020						
4	24030						
5	24110					Strike plate: GLUTZ 22820	
Reference test reports: 14/03-A108-B2 dated 03.08.2015 2019-07-0417-B2 dated 09.12.2019 2019-07-0417-K2 dated 09.12.2019 2021-07-0185-G2 dated 08.03.2021 2021-07-0185-K2 dated 08.03.2021							
6	12300	I	50-80 mm	RZ 74, 78 mm PZ 72, 78, 88 mm	18/20/24 x 3 mm	Strike plates R1	3 7 6 B 1 3 2 1 A/B B
7	12310	IV					
8	12340	III					
9	12400	I IV					
10	12410	I I					
11	12501	I					
12	12500	IV					3 7 6 B 1 3 2 1 A/B A
13	12402	I					
14	12412	I					
15	12100	IV	Strike box			Forend R2 Accessories double-leaf R3	3 7 6 B 1 3 2 1 A/B C
Reference test reports: 2020-07-0308-G2 dated 22.03.2021 2020-07-0308-K2 dated 22.03.2021 2021-07-0550-G2 dated 23.06.2022 2021-07-0550-K5 dated 23.06.2022 2021-07-0550-K6 dated 23.06.2022							

Annex 1 **Page 3 of 8**
Certificate holder: **Glutz AG**
Date of issue: **22.03.2023**



Certificate No.: 0757-CPR-229PANIK-6014391-4-9

Itd. Nr.	Item	Function	Backset	Distance	Forend	Accessories	Classification
16	18945	I	60-80 mm	RC 74, 78, 94 mm PC 72, 78, 88, 92 mm	18/20 x 3 U24x6x2	Strike plates R4 R5	3 7 6 B 1 3 2 1 A B
17	18947						
18	18905						
19	18990						
20	18995						
21	18962	IV					
22	18970	V					
23	18971	V					
24	18907	V					
25	18970HZ					U24x6x2 mm	
26	18971HZ						
Reference test reports: 14-002910-PR01 dated 24.02.2015 14/08-A295-B2 dated 18.04.2016 17/08-A337-G2 dated 01.09.2017 107 2017 01 dated 16.10.2017 2020-07-0212-G2 dated 03.03.2021 2020-07-0212-K2 dated 21.04.2021 2020-07-0308-G2 dated 22.03.2021 2020-07-0308-K2 dated 22.03.2021 2020-07-0763-G3 dated 08.03.2021 2020-07-0763-K3 dated 21.04.2021 2022-07-0324-G2 dated 23.06.2022 2022-07-0324-K2 dated 23.06.2022							

Certificate of constancy of performance

Annex 1
Certificate holder: Glutz AG
Date of issue: 22.03.2023



Certificate No.: 0757-CPR-229PANIK-6014391-4-9

Strike plates and accessories

R1

	Strike plates 12300 12310 12340 12400 12410 12500 12501																													
	B-1001.131	B-1001.440	B-1001.431	B-1001.700	B-1102.440	B-1102.701	B-1120.131	B-1130	B-1133	B-1138	B-1150.702	B-1151.712	B-1151.711	B-1151.713	B-1307.131	E-1130	E-1151	16000	16010	16020	16600	16610	16620	16630	13043	13024	13023	B-22400*	B-22610*	
PZ72/RZ74	x	x	x	x	x	x		x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x
PZ78/RZ78		x	x		x		x	x	x	x	x	x	x	x		x	x	x	x	x	x	x	x	x					x	x
PZ88								x	x	x						x		x	x		x	x	x	x						
Burglary resistance EN 1125 class 2 (1000N)	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
*only 12500 and 12501 Reference test reports: 2021-07-0028-G2 dated 22.04.2021 2021-07-0550-G2 dated 23.06.2022																														

R2

Forend strike box 12100	Burglary resistance EN 1125 class 2 (1000N)
12110.1.15 24r x 235mm	2
12110.1.17 20r x 235mm	2
12110.2.22 24r x 65 x 235mm	2
12110.2.23 24r x 36 x 235mm	2
12110.3.33 20r x 12r x 235 mm	2
Reference test reports: 2021-07-0550-G2 dated 23.06.2022	

Annex 1 **Page 5 of 8**
Certificate holder: **Glutz AG**
Date of issue: **22.03.2023**



Certificate No.: 0757-CPR-229PANIK-6014391-4-9

R3

Accessories strike box 12100		
Product-#	Designation	Additionally usable
11021	Latch	BKS: 1895 Assa Abloy MSL: 1730 Wilka 4685
13825	Bolt striking plate	Assa Abloy MSL: 1728
13824	Bolt striking plate	Assa Abloy MSL: 1731
11031	Top locking bar M6 connection thread	Assa Abloy MSL: 1725 BMH: 1101
11036	Bottom locking bar M6 connection thread	Assa Abloy MSL: 1724 BMH: 1100
11037	Bottom locking bar for Planet M6 connection thread	Assa Abloy MSL: 1724 Planet
11041	Bolt guide plate	BKS: B-9019 Assa Abloy MSL: 1726 Wilka 9653
11051	Floor socket	BKS: B-9009 Assa Abloy MSL: 1727 Wilka: 9651
(-)	Floor socket extender	Wilka: 9652 WSS: 07.230.0000.310

Reference test reports:
2021-07-0550-G2 dated 23.06.2022

R4

	Main strike plates MINT 18945 18990 18995 18962 18970 18971 18907 18947 18905														
	B-1130	B-1133	B-1138	B-1150.702	E-1130	E-1151	16000	16010	16020	16030	16040	16600	16610	16620	16630
PZ72/RZ74	x	x	x		x		x	x		x	x	x	x	x	x
PZ78/RZ78	x	x	x	x	x	x	x	x	x			x	x	x	x
PZ88	x	x	x		x		x	x				x	x	x	x
PZ92/RZ94	x	x	x		x		x	x				x	x	x	X
EN 1125 class 2 (1000N)	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
Reference test reports: 2021-07-0028-G1 dated 23.04.2021															

Annex 1 **Page 6 of 8**
Certificate holder: **Glutz AG**
Date of issue: **22.03.2023**



Certificate No.: 0757-CPR-229PANIK-6014391-4-9

R5

	Additional strike plates MINT 18945 18990 18995 18962 18970 18971 18947						
	B-1153-720	B-1131	B-1132	B-1134	B-1135	B-1137	16050
PZ72/RZ74		x	x	x	x	x	x
PZ78/RZ78	x	x	x	x	x	x	
PZ88		x	x	x	x	x	
PZ92/RZ94		x	x	x	x	x	
EN 1125 class 2 (1000N)	2	2	2	2	2	2	2
Reference test reports: 2021-07-0028-G1 dated 23.04.2021							

R6

	Main strike plates MINT HZ 18970HZ 18971HZ							
	B-1133	B-1138	16000	16010	16030	16040	16600	16610
PZ72/RZ74	x	x	x	x	x	x	x	x
EN 1125 class 2 (1000N)	2	2	2	2	2	2	2	2
Reference test reports: 2022-07-0324-G2 dated 23.06.2022								

Certificate of constancy of performance

Annex 1
Certificate holder: Glutz AG
Date of issue: 22.03.2023

Page 7 of 8



Certificate No.: 0757-CPR-229PANIK-6014391-4-9

R7

	Additional strike plates MINT 18970HZ 18971HZ		
	B-1134	B-1137	16050
PZ72/RZ74	x	x	x
EN 1125 class 2 (1000N)	2	2	2
Reference test reports: 2022-07-0324-G2 dated 23.06.2022			

Permitted push-bars and touch-bars

Manufacturer	Products Certificates
Glutz	8615
ECO	EPN 2000 II, EPN 2000 III, EPN 900 IV

Reference test reports:
2021-07-0550-G2 dated 23.06.2022

Certificate of constancy of performance

Annex 1 Page 8 of 8
Certificate holder: Glutz AG
Date of issue: 22.03.2023



Certificate No.: 0757-CPR-229PANIK-6014391-4-9

Max. door leaf weight:	200 kg
Max. door leaf width:	1,320mm
Max. door leaf height	2,520mm
Function I:	Solid lock follower, continuous escape door function Opening from the inside is always possible with action of the hardware. Opening from the outside is possible with action of the key on the latchbolt. (Trafo-) emergency function E
Function II:	Split lock follower, continuous escape door function from the inside Opening from the inside is always possible with action of the hardware. Opening from the outside is possible with action of the key/locking cylinder on the latchbolt.
Function III:	Split lock follower, continuous escape door function from the inside Opening from the inside is always possible with action of the inside hardware. Outside hardware always engaged or disengaged with action of the key. Bolt operated from the outside <u>only</u> with action of the key. After hardware operation from the inside the door can be opened also from the outside until manual re-bolting. Access function D
Function IV:	Split lock follower, continuous escape door function from the inside Opening from the inside is always possible with action of the inside hardware. Outside hardware always engaged or disengaged with action of the key. Bolt operated from the outside <u>only</u> with action of the key. After hardware operation from the inside the door cannot be opened from the outside even with action of the hardware. Emergency function B
Function V:	Split lock follower, continuous escape door function from the inside Opening from the inside is always possible with action of the inside hardware. The outside hardware is normally disengaged. The outside hardware can be engaged only via a specific key position. The outside hardware is disengaged again after the key has been removed. Enforced closure function C.
VS-Type A:	Device for active leaf of double leaf doorsets and for single leaf doorsets
VS-Type B:	Device for single leaf doorsets:
VS-Type C:	Device for inactive leaf of double leaf doorsets
Note 1:	As set out by the German Building Code a VS-Type B device as per DIN EN 179 (device for single leaf doorsets only) can be used also for the active leaf of a double leaf doorset, provided: a) the device of the inactive leaf is protected against abuse, and b) the clear opening width of the active leaf is sufficient to be used as escape width.
Note 2:	Type C devices, devices only for the inactive leaf of double leaf doorsets, were tested for verification of grade 7 of durability (2nd digit) as per EN 179, applying only 20,000 test cycles.