

Declaration of Performance

LE/DoP-Nr. 004E/CPR/2017-01-16

1. **Unique identification of the product type:** Mortise latchlocks
series SL4540-SL4640 / SL4541-SL4641
series SL4828-SL4838 / SL4828NCF-SL4838NCF / SL4742-SL4743
2. **Intended use:** Mechanically operated locks, on application with an appropriate door closing device, for application on fire and / or smoke control doors.
3. **Manufacturer:** Glutz Ltd.
Segetzstrasse 13
CH-4502 Solothurn
Switzerland
4. **Authorised representative:** N/A
5. **Systems of assessment of constancy of performance:** System 1
6. **Harmonised standard:** EN 12209: 2003+AC:2006
Notified body: ift Rosenheim NB-Nr. 0757 has issued the Certificate of constancy of performance with the number 0757-CPR-230-6014391-1-1 to system 1 and essential characteristics assessed from 7.1 to 7.4.
7. **Declared performance:**

Essential characteristics	Performance	Harmonised technical specification
7.1 Self-closing ability	Fulfilled, grade 5 (door mass up to 200kg, door closing force max. 25N)	5.4.2 und 5.1.2, EN 12209: 2003+AC: 2006
7.2 Durability of self-closing action	Fulfilled, grade X (200'000 cycles, 120N load on latch bolt)	5.3.1, EN 12209: 2003+AC: 2006
7.3 Ability to maintain door in closed position and not contribute to the spread of fire	Fulfilled, grade 3 determined duration of fire resistance 90 minutes (PB-Nr.: 188576 / A from 23.02.2010)	5.2.1 und 5.5, EN 12209: 2003+AC: 2006
7.4 Control of dangerous substances	-	5.1.1, EN 12209: 2003+AC: 2006

8. The performance of the actual product is in conformity with the declared performance / performances. The issue of the declaration of performance complying with regulation (EU) nr. 305/2011 is under the sole responsibility of the above named manufacturer.

Signed for and on behalf of the manufacturer by:

ppa. Rolf Allemann, Product Manager Locks

Solothurn, 16.01.2017

